

VALVE REFACER

PRODUCT DESCRIPTION: RV 3000

The RV3000 valve refacer has a double "V" operation, instead of the traditional use of pliers or chucks and gives very accurate results. The unique valve locking system can be applied on a wide range of engines.

BASIC EQUIPMENT

Allen wrench 2.5/3/4/5/6
Open end wrench 8
Valve drassing wheel
Valve stop
Diamond
Diamond support and valve and refacer

OPTIONS

Other eletric powers on request
Adapter for valve stem lower than \varnothing 4
and lower than 70 mm length
Pair of valve supports for valve stems over \varnothing 16 mm

MAIN SPECIFICATIONS

Valve stem diameter	4 mm (5/32") - 16 mm (10/16")
Grinding sngle	20°-60°
Maximum head diameter	100 mm
Maximum head length	400-450 mm
Valve length at 30° and 40°	75 mm min
Head diameter 30°	22 mm min
Head diameter 45°	11 mm min
Grinding wheel size	175 \varnothing x 30 mm
Grinding wheel speed	2800 rpm
Elettric power	230/400V 50Hz 3Ph
Valve dragging wheel speed	14 rpm
Dimension	800(31" 1/2) x 600(23" 3/5) x 600(23" 3/5)
Weight	109Kg (240Lbs)
Low tension driving control	
Motor-driven grinding wheel	